# **CHEMICALS**

5-WAY PLUS™ PENETRANT

Penetrates, lubricates, demoisturizes,

Frees rusted, frozen nuts and bolts

Excellent for precision instruments

Undercuts grit and grime on metal

surfaces leaving a protective film

Displaces moisture in electrical

apparatus, generators, motors

Ideal for stainless steel and aluminum

cleans and prevents rust

of moulding dies and

extension screws

Inhibits corrosion and pitting

#### LU103 RUST BREAKER<sup>TM</sup> **HEAVY DUTY RUST PENETRANT**

- Quickly loosens rust while penetrating grease and dirt
- Transparent, non-staining oil Light film displaces moisture and
- acts as a corrosion preventative Jet stream sprays up to two feet
- for safe, accurate application Flashpoint: 205°F
- Will not harm painted surfaces
- For releasing rusted or frozen lugs and bolts, lubricating tight-fitting parts, general overhaul, repair work, food plant equipment



Price

/Each

A

A

#### **TKX ALL-PURPOSE** LUBRICANT

- Non-flammable CO, propellant
- Displaces moisture
- High flash point of 175°F (79°C)
- Protects against corrosion
- Loosens rusted or frozen parts
- Does not contain chlorinated solvents or silicones
- Safe on most surfaces Inverta spray valve lets
- you spray in all directions NSF registered category code H2
- Provides non-drying long-lasting, oily film



<b>—</b>			
lodel	Mfg.		Price
lo.	No.	Size	/Each
A846	C02016	11 oz.	
B490	C02028	1 gal.	
B638	C02005	5 gal.	
B639	C02055	55 gal.	

### LST PENETRANT

Size

10 oz.

Specially formulated with low surface tension for fast penetrating action

Mfg

SC0103000

No

AA113

- Attacks rust and corrosion to free frozen parts
- Powerful foaming action provides complete surface coverage
- Displaces moisture Lubricates and protects
- metal surfaces
- Flash point of 175°F (79°C) Inverta spray valve lets
- you spray in all directions NSF registered category code H2

## PENETRATING OIL

- Flashpoint: 60.6°C
- Slow evaporation rate A no-compromise penetrant that attacks corrosion to free corroded fasteners and mechanical components
- A super-fast, powerful, concentrated penetrating solvent that loosens and cleans
- Instantly penetrates tightly fitted crevices
- NSF Registered H2

CR©

Mode

YB991

Price

/Each





Quickly releases rusted and corroded nuts, bolts, hinges and other frozen components

Size

24 oz.

/Each

ATTIT COM

- Extremely high solvency,
- low surface tension Enhanced penetration

Node

AA505

Nn

- and lubrication Outperforms the competition
- in independent lab tests Penetrates faster and deeper
- than most other similar products in the market place
- Inverta spray valve

Maximum Working

Can also be used as a

multi-purpose lubricant

Temperature: 141°F (61°C)

Ideal for rusted and frozen metals

- NSF registered category code H2
- VOC compliant



Model No.	Mfg. No.	Size	Price /Each
AD970	C02316	13 oz.	
AD297	C02322	20 oz. trigger	

#### **WD-40**

Ļps

Ande |

AA843

- Loosens rusted parts
- Displaces moisture

Mfg

C01916

No

- Non-conductor, dries out electrical and electronic equipment
- Stops squeaks
- Lubricates and protects against moisture and corrosive
- Operating temperature: -50°F to 300°F
- Minimum flash point 110°F open cup

W	<b>D-4</b> (	
masso		

Product of Long march of California			
Model	Mfg.		Price
No.	No.	Size	/Each
NA611	01111	11 oz. aerosol	
NA609	01010	3.785 L	
NA608	01000	Spray bottle empty	

Size

11 oz.

#### **BOLT-OUT™**

Mfg.

73060

No

- Penetrates then lubricates Faster disassembly
- with less effort
- Inhibits further rust
- **Displaces** moisture
- No chlorinated solvents
- Non-flammable liquid formula
- Effective at wide temperature range

#### 

	-		
Model No.	Mfg. No.	Size	Pri /Ea
YC429	53-D 892	400 ml	
AC310	53-D 893	500 ml trigger	
AA479	53-D 897	20 L	
AC311	53-D 898	200 L	

Size

312 g



/Eac

e h	CRC

#### Mfg. /lode Price Size /Each No AF244 75330 312 g

